

Homogeneous Vinyl

# sphera® elite







areas, adding style to every project where the ability to withstand heavy traffic and providing a healthy and hygienic solution are key. The SMART-top surface protection provides excellent stain and scratch resistance properties with superior appearance retention, ensuring the floor looks good and performs well for years to come.

## Innovative design

Sphera Elite has a sophisticated appearance through its subtle reference to natural materials, and it's organic pattern will transform any public space into an inviting place. Sphera Elite guarantees performance thought its lifetime with its forgiving design and extremely durable and lightweight construction. Whether in demanding healthcare environments, flexible multi-purpose modern public buildings, education facilities or offices, Sphera Elite offers a durable and innovative solution.

## *Creating better environments*

The Sphera production process aims to avoid any unnecessary waste and minimise energy and raw material use. Any waste that may be produced from Sphera premium homogeneous sheet vinyl is reused in Forbo's other premium products. Sphera is phthalate free and produced with 100% renewable electricity, with minimal impact on the environment.

Sophisticated, organic design.

Calming and reconnecting to nature.

Creating a sense of ease in any commercial interior.

Designed to last, even in the most demanding of environments.



## DESIGN 🛆 COLOUR

- A subtle blend of soft, organic shapes and calming colours.
- Metallic traces of gold, chrome or copper for a subtle yet sophisticated design.
- Colour coordinated with other Forbo sheet vinyl ranges, such as Eternal and Step.
- Non-directional design.

## PERFORMANCE \(\triangle \) DURABILITY



- Balanced new product development with high PVC and low filler content, resulting in the highest quality product and lasting
- SMART-top finish specifically designed for enhanced cleanability and ability to withstand heavy use.
- Increased flexibility and lower weight to allow for easy fitting and
- Excellent stain resistant surface treatment and high quality scratch resistant properties.



## TECHNOLOGY A SUSTAINABILITY

- Low emissions and phthalate free manufacturing contribute to a healthy indoor environment.
- New technology powered by green renewable energy delivers consistent quality in an efficient and sustainable way with zero
- Carefully selected raw materials offer possibilities for re-use
- Low energy and water use thanks to the efficient state-of-the-art production process.

## **sphera**® elite



sphera® elite








LRV 55 **50480** | selenite



**50481** | seiryu LRV 40



**50483** | hematite LRV 25




**50482** | smokey quartz LRV 14






**50489** | pyrite LRV 13




**50484** | coquina **50489** | pyrite **50488** | brown topaz



LRV 50 **50486** | sardonyx




**50488** | brown topaz



**50487** | axinite LRV 26




**50484** | coquina LRV 44




**50485** | obsidian LRV 27



**50490** | enstatite



**50491** | citrine



LRV 27

LRV 25

**50493** | iris agate

## **sphera**<sup>®</sup> elite






## **sphera**<sup>®</sup> elite






















LRV 27

**50492** | jadeite





LRV 27

**50497** | zircon

## **Technical specifications**



Sphera Elite meets the requirements of EN ISO 10581

×	Total thickness EN ISO 24346  Surface finish		2.0 mm SMART top		
	Binder content	EN ISO 10581	Type 1		
	Collection size		18		
ΔŮ	Domestic use	EN ISO 10874	Class 23		
<i>î</i>	Commercial use	EN ISO 10874	Class 34		
iii)	Light industrial use	EN ISO 10874	Class 43		
	Roll width	EN ISO 24341	2.0 m		
	Roll length	EN ISO 24341	≤ 27 m		
ß	Total weight	EN ISO 23997	2750 g/m²  ≤ 0.4 %  ~ 0.2 %  R9  Pass  ≤ 0.10 mm  ~ 0.03 mm		
K N	Dimensional stability Typical value	EN ISO 23999			
The second	Slip resistance (ramp test)	DIN 51130			
	Castor chair continuous use	ISO 4918			
	Residual indentation Typical value	EN ISO 24343-1			
_ 勃	Colour fastness to light	EN ISO 105-B02 method 3	≥7		
	Indoor Air Emissions: TVOC after 28 days	EN 16516	≤ 0.01 mg/m³		
FO	Resistance to chemicals	EN ISO 26987	Very good		
9	Flexibility	EN ISO 24344	Ø 10 mm		
	Use in wet areas	EN 13553	Yes		
<b>_</b>	Bacteria resistance	EN ISO 846	Does not support growth		
LCA	Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact		
<b>(</b>	Creating better environments				
Ť	Renewable electricity		Sphera Elite is manufactured using 100% electricity from renewable sources		
OTHE FLOOR	Back to the Floor		Installation off cuts can be collected and recycled via Back to the Floo		
	SKA		Sphera Elite meets SKA Rating criteria for M12 for soft floor coverings in office, retail and higher education schemes.		
	Sphera Elite meets the requirements of EN	14041:2004	O200301-0		
L CS	Reaction to fire	EN 13501-1	B <sub>n</sub> -s1, L, CS		
9/5 10.30	Slip resistance	EN 13893	µ≥ 0.30		
λ <sub>23</sub>	Thermal conductivity	EN 12524	0.25 W/mK		
75Å	Body voltage	EN 1815	≤ 2.0 kV		



All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

## BREEAM ratings Sphera Elite

opiicia ziite					
Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)
A	A+	A+	A	A+	A+

Forbo Flooring UK Limited High Holborn Road, Ripley, Derbyshire, DE5 3NT

## London EC1 showroom

79 St John Street, Clerkenwell London EC1M 4NR Tel. 0207 553 9300

### For commercial enquiries:

If calling from the North, London & South East Tel. 0800 0282 162

If calling from Scotland, Midlands & South West Tel. 0800 0935 258

## Nuway enquiries:

## Residential enquiries:

E-mail: info.flooring.uk@forbo.com www.forbo-flooring.co.uk

## Samples: Tel. 0800 731 2369 Email: samples.uk@forbo.com

### Ireland

Forbo Ireland Ltd. 2 Deansgrange Business Park Blackrock Co Dublin Tel. 00353 1 2898 898 E-mail : info.ireland@forbo.com www.forbo-flooring.ie

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co. uk for up-to-date details or corrections to such contents.

### Registered office:

Forbo Flooring UK Limited High Holborn Road - Ripley Derbyshire DE5 3NT Registered in England 9200318



0800 731 2369







